

Serial No.: 09/911,353
Docket No.: VAS-5644
Amendment dated December 19, 2003
Responsive to Office Action of November 28, 2003

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

5

Listing of claims:

1. (Original) A stent or stented graft compliance test assembly, comprising:
an animal tissue tube having opposed free ends and defining an inner lumen;
10 a pre-tester including fixtures adapted to sealingly couple to the free ends of the animal tissue tube and a fluid supply in communication with at least one of the fixtures and the animal tissue tube lumen; and
a stent or stented graft positioned within the animal tissue tube.
- 15 2. (Original) The assembly of claim 1, wherein the animal tissue is porcine.
3. (Original) The assembly of claim 2, wherein the animal tissue tube is a section of porcine aorta with any side branches ligated.
- 20 4. (Original) The assembly of claim 1, further including a pulsatile pumping system for the fluid supply that pressurizes the animal tissue tube lumen to pressures found in the human vascular system.
- 25 5. (Original) The assembly of claim 1, further including a sensor for measuring the exterior diameter of the animal tissue tube.
6. (Original) The assembly of claim 5, wherein the sensor is a non-contact sensor.
7. (Original) The assembly of claim 6, wherein the sensor is a laser micrometer.

Serial No.: 09/911,353

Docket No.: VAS-5644

Amendment dated December 19, 2003

Responsive to Office Action of November 28, 2003

8. (Original) The assembly of claim 5, wherein the assembly includes a stented graft having multiple individual wires at axially spaced locations along an outer graft tube, and wherein the sensor is positioned to measure the exterior diameter of the animal tissue tube at the axially spaced locations.

9. (Original) A method of testing the compliance of a stent or stented graft, comprising:
sealingly coupling opposed free ends of an animal tissue tube onto fixtures of a pre-tester, the animal tissue tube having a lumen;
positioning a stent or stented graft within the animal tissue tube; and
providing a fluid to the animal tissue tube lumen via at least one of the fixtures.

10. (Original) The method of claim 9, further including pressurizing the fluid in the animal tissue tube lumen to pulsatile pressures found in the human vascular system.

11. (Original) The method of claim 10, further including measuring the exterior diameter of the animal tissue tube at different pressures.

12. (Original) The method of claim 11, further including:
recording the data on the measured exterior diameter of the animal tissue tube;
sealingly coupling opposed free ends of a synthetic tube onto fixtures of a tester, the synthetic tube having a lumen;
positioning within the synthetic tube a stent or stented graft of the same kind as was pre-tested in the animal tissue tube;
providing a fluid to the synthetic tube lumen via at least one of the fixtures of the tester;
pressurizing the fluid in the synthetic tube lumen at a pulsed rate; and

Serial No.: 09/911,353
Docket No.: VAS-5644
Amendment dated December 19, 2003
Responsive to Office Action of November 28, 2003

measuring the exterior diameter of the synthetic tube and controlling the fluid pressure based on the recorded data.

13. (Original) The method of claim 12, wherein the fluid pressure within the synthetic tube lumen is controlled to expand the diameter of the synthetic tube to the same dimension as the measured diameter of the exterior diameter of the animal tissue tube.

14. (Original) The method of claim 13, wherein the animal tissue tube lumen is pressurized to both normal and abnormal pulsatile pressures found in the human vascular system, and the synthetic tube lumen is pressurized at a pulsed rate based on the measured exterior diameter of the animal tissue tube to simulate both normal and abnormal compliance conditions.

15. (Original) The method of claim 9, wherein the step of positioning comprises positioning in the animal tissue tube a stented graft having multiple individual wires at axially spaced locations along an outer graft tube, and further including:

pressurizing the fluid in the animal tissue tube lumen to pulsatile pressures found in the human vascular system; and

measuring the exterior diameter of the animal tissue tube at the axially spaced locations and at different pressures.

20

16. (Original) The method of claim 15, further including:

recording the data on the measured exterior diameter of the animal tissue tube;

sealingly coupling opposed free ends of a synthetic tube onto fixtures of a tester, the synthetic tube having a lumen;

25

positioning within the synthetic tube a stented graft of the same kind as was pre-tested in the animal tissue tube;

providing a fluid to the synthetic tube lumen via at least one of the fixtures of the tester;

pressurizing the fluid in the synthetic tube lumen at a pulsed rate; and

Serial No.: 09/911,353
Docket No.: VAS-5644
Amendment dated December 19, 2003
Responsive to Office Action of November 28, 2003

5 measuring the exterior diameter of the synthetic tube at the axially spaced
locations while controlling the fluid pressure based on the recorded data such that the
diameters of the synthetic tube at the axially spaced locations expands to the same
dimensions as the measured diameter of the exterior diameter of the animal tissue tube at
the axially spaced locations.

Claims 17-20 are cancelled herewith